



Features

- Supports up to 32 devices
- Supports local & remote monitoring
- Supports RS485, Ethernet DI/DO, AI, USB2.0 ports

Model	RCM-Logger-Z
System Information	
Supported models	RCM 275-TP-M-HV
Max. connected devices	32 units
No. of LEDs	LED *18 (Power supply *1/RS485*8/4G*2/CAN*2/Internet*2/Heart Beats*1)
Communication Parameters	
Communication Methods	Ethernet
User interface	PC
Frequency	2.4GHz (a/b/g/n)
Data Uploading Interval	5 Mins (1-5 Mins Configurable)
Communication ports	RS485*4, Ethernet*2, DI*4, DO*2, AI*4, USB 2.0*1
Communication Protocol	Ethernet: Modbus-TCP, IEC 104, IEC 61850MMS/GOOSE; RS485: MODBUS-RTU/DL-T645
Smart Access	Support
Third-party Devices	Smart meter, Weather station, Temperature & Humidity sensors
Electrical parameters	
Operating Voltage	24Vdc
Power Consumption	≤ 15W
General Data	
Protection level	IP20
Operating Temperature	-30~60°C
Humidity	0~95%
Installation Method	Wall Mounted & Rail
Si-Logger Certification	CE

*Smart Access: The Data logger can automatically identify the accessed devices, and addressed the devices, no manual setup is required.

